



LIGHTCONVERSE PRICE LIST 2012


Hardware «LIGHTCONVERSE-SERVER»

		Power of visualisation @44 FPS	Video-inputs	Video-resolution @60Hz	Video-output for virtual cameras and mapping	Export Price, EUR (VAT not included)
	SERVER-STUDIO	1536 fixtures 96 universes	1x HDMI/DVI-D, Component, Composite, SDI, HD-SDI	26.5 megapixels 15x 1680x1050	3x DVI-I 12x DVI-D	16580
	SERVER-MAPPING	1536 fixtures 96 universes	1x HDMI/DVI-D, Component, Composite	10.5 megapixels 6x 1680x1050	3x DVI-I 3x DVI-D	13325



Software «LIGHTCONVERSE»

	Onboard control	Max Fixtures per project	Ethernet universes: sACN-in, ArtNet-in/out	Video input/playback, Hippotizer, Pangolin Lasers, Lasergraph DSP, Avolites ACDI, HES Wholehog III, Grand MA 1/2	Dynamic layers (DMX controlled moving, rotation, scale). Laser scanning and tracking-control	Video-output for virtual cameras and mapping. 3D-R output for stereo-projection	Export Price, EUR (VAT not included)	
	UNLIMITED	Yes	1536	96	Yes	Yes	2	4800
	TRACE	Yes	512	96	Yes	Yes	1	2800
	Media	Yes	512	96	Yes	No	No	1400
	Net-In	No	512	96	No	No	No	700
	Design	Yes	512	No	No	No	No	400

Laser tracking-sensors «LIGHTCONVERSE»

	Coverage Radius	Coverage Angle	Motion Latency	Tracking Object's Minimum size	Connection interface	Laser and protection class	Export Price, EUR (VAT not included)
 Laser Radar-4	55 m	188°	23 ms	2cm @4m 10cm @15m	Ethernet 100 MBit/s	1 (EN 60825-1) IP 65, 0..+50°C	5830

DMX-512 USB-interfaces

		Output DMX channels			Input DMX channels		Description	Export Price, EUR (VAT not included)
		out-1	out-2	out-3	in-1	in-2		
	Replay - 256	256	-	-	256	-	DMX controller/interface. Flash memory on 20 programs, 24 scenes each. PS/2 keyboard connection. Can work like DMX-in for LightConverse or DMX-out. May be programmed from a DMX control desk also. USB or external powering.	500
	Replay - 512	512	-	-	512	-		600
	LIGHTCONVERSE - 1536X	512	512	out-2	512	-	Interface for professional use. 2 USB connectors. 3 pin XLRs. USB data isolated, USB power grounded. Power supply.	680
	LIGHTCONVERSE - 2048X	512	512	-	512	512		750

* Shipment Ex-Works Osnabrueck, Germany